## Table: VRRP interval example 3 settings

	Settings on NS1	Settings on NS2	Settings on NS3
VIP addresses			
VIP1 (for reference purposes only)	<ul> <li>IP address: 192.0.1.10</li> <li>VRID: 10</li> <li>Priority: 90</li> </ul>	<ul> <li>IP address: 192.0.1.10</li> <li>VRID: 10</li> <li>Priority: 30</li> </ul>	<ul> <li>IP address: 192.0.1.10</li> <li>VRID: 10</li> <li>Priority: 60</li> </ul>
VIP2 (for reference purposes only)	<ul> <li>IP address: 192.0.1.20</li> <li>VRID: 20</li> <li>Priority: 100</li> </ul>	<ul> <li>IP address:</li> <li>192.0.1.20</li> <li>VRID: 20</li> <li>Priority: 300</li> </ul>	<ul> <li>IP address:</li> <li>192.0.1.20</li> <li>VRID: 20</li> <li>Priority: 200</li> </ul>
VIP3 (for reference purposes only)	<ul> <li>IP address:</li> <li>192.0.1.30</li> <li>VRID: 30</li> <li>Priority: 70</li> </ul>	<ul> <li>IP address:</li> <li>192.0.1.30</li> <li>VRID: 30</li> <li>Priority: 140</li> </ul>	<ul> <li>IP address: 192.0.1.30</li> <li>VRID: 30</li> <li>Priority: 210</li> </ul>
Communication Intervals			
Hello Interval	400 milliseconds	400 milliseconds	400 milliseconds
Dead Interval	1 second	2 seconds	3 seconds